



LINEAR J MULTISPIRE WELDED

* New high efficiency lamps in Energy Class C (except for 01993 item): energy saving up to 20% more compared to previous versions.

* The multispire technology makes it possible to considerably reduce the risk of filament breakage.

* Sizes: 78 mm and 118 mm; wattages from 60W to 400W.

* Anti-shattering glass required in accordance with European regulations for EN 60598 appliances.

* Working position: universal.

Item Characteristics

	Code	01974-ES
	Lamp Voltage	230 V
	Nominal Power	80 W
	Base	R7s-15
	Lamp Current	0,34 A
	Nominal Flux	1380 LUMEN
	Rated Flux	1380 LUMEN
	Type of lamp	78mm
	Colour temperature	3000 K
	Diameter	10 mm
	Lenght	78 mm
	Colour	
Performance		
	Irc/Ra	100
	Lifetime	1000 h
	Energy Class	C
	Equivalence with incandescent lamp	104 W
Tech Info		
	Dimmerable	YES
	Operating Position	360°
	Closed fittings only	YES
	Number of ON-OFF cycles	15000
	Power Factor	1
	Warm-up time up to 60 % of the full light output	Instant Full Light
	Lamp start time	< 1 sec.
	LLMMF - Lamp lumen maintenance factor	80
	Fulfilled Directives and norms	2006/95/CE ;2009/125/CE ;2002/95/CE ;EN 60432-3+A1 ;EN 60432-3+A2 ;244/2009 ;

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.



Shipping info

Pack	25 pz
Dim.pack height	12 cm
Pack lenght	10 cm
Pack depth	12 cm
Item barcode	8011905827731
Master barcode	8011905773014

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.