

PAR56 FOR SWIMMINGPOOL



- * Specialist lamp for underwater applications; use only inside suitable fittings.
- * Screw terminals.
- * Clear glass finish.
- * For swimmingpools, fountains and other under water applications.
- * Max depth underwater: 1.0 mt.

Item Characteristics

	Code	30012PAR56FL
	Lamp Voltage	12 V
	Nominal Power	300 W
	Base	screw/a vite
	Lamp Current	25 A
	Rated Flux	LUMEN
	Colour temperature	2700 K
	Lumen	2X38°
	Diameter	177 mm
	Lenght	110 mm
	Colour	
Performance		
	Irc/Ra	100
	Lifetime	1000 h
Tech Info		
	Dimmerable	YES
	On another Desition	0000
	Operating Position	360°
	Closed fittings only	YES
	•	
	Closed fittings only	YES
	Closed fittings only Number of ON-OFF cycles	YES 6000
	Closed fittings only Number of ON-OFF cycles Power Factor Warm-up time up to 60 % of the full	YES 6000 1
Shipping info	Closed fittings only Number of ON-OFF cycles Power Factor Warm-up time up to 60 % of the full light output	YES 6000 1 Instant Full Light
Shipping info	Closed fittings only Number of ON-OFF cycles Power Factor Warm-up time up to 60 % of the full light output	YES 6000 1 Instant Full Light
Shipping info	Closed fittings only Number of ON-OFF cycles Power Factor Warm-up time up to 60 % of the full light output Lamp start time	YES 6000 1 Instant Full Light <1 sec.
Shipping info	Closed fittings only Number of ON-OFF cycles Power Factor Warm-up time up to 60 % of the full light output Lamp start time Pack	YES 6000 1 Instant Full Light <1 sec.
Shipping info	Closed fittings only Number of ON-OFF cycles Power Factor Warm-up time up to 60 % of the full light output Lamp start time Pack Dim.pack height	YES 6000 1 Instant Full Light <1 sec. 6 pz 17 cm
Shipping info	Closed fittings only Number of ON-OFF cycles Power Factor Warm-up time up to 60 % of the full light output Lamp start time Pack Dim.pack height Pack lenght	YES 6000 1 Instant Full Light <1 sec. 6 pz 17 cm 31.5 cm
Shipping info	Closed fittings only Number of ON-OFF cycles Power Factor Warm-up time up to 60 % of the full light output Lamp start time Pack Dim.pack height Pack lenght Pack depth	YES 6000 1 Instant Full Light <1 sec. 6 pz 17 cm 31.5 cm 46 cm

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.